



July 11th 1894
 I commenced Survey of Section
 4, 5, 8, 9 Town 7 North,
 Range 6 West.
 E. J. Cox
 County Surveyor.

COURSE. DISTANCE. REMARKS.

On the request of the Trustees of Grant and South
 Township, and on ten days notice being given by said
 Trustees of the date of said Survey. I commenced Survey
 to locate the Section Lines between Sections 4, 5, 8, 9
 T. 7. R. 6. I commenced at the ~~North~~ East Corner Section
 5 T. 7 R. 6. (See field notes on page 133 for this corner)
 Thence South 161.52 Chains to the South East corner
 Section 8 to a corner all ready established. Thence
 Set. returned 79.52 Chains and set stakes for corner
 SE Section 5. I had previously in running a line
 commencing at a stone set the North East corner of
 Section 9. by W. H. Clayton and running west 159.00
 to a stone set for the South west corner of Section
 5 by a Surveyor by the name of Plummer. I understood
 36.2 Chains to my right continued Chain line at 200.00
 to the S. E. corner set & located by J. B. Kelshum in 1838
 I question the correctness of this corner. it should be in accordance
 with field notes of original Survey South of this place
 yet I had to accept it as an old corner
 Returned 120.30 and corrected stake heretofore set and
 located the corner of Sections 4-5-8 & 9. by placing

Corners Established.	Monument.	Bearing Trees.	Diameter in Inches.	Course.	Links Distant.
an oak post 4 feet in length 3 feet in the earth set by	Maple	4	N 65° 11' W 08		
	do	6	N 72° E 32		
I then proceed to place a stake at each 10 chains on line between Section 4, 5, 8, 9. to enable them to cut out line of road. I also made a corner E 1/4 Sec 8 Stone Susafra 9 S 84° W 80 1/2					
E 1/4 NE Sec 8 Stone	Hickory	16	S. 84° E 57		
E 1/4 Sec 8 post	Hickory	12	S 52 1/2° E 48		
nothing further being demanded I adjourn Survey					

E. J. Cox
 Surveyor Grant County